



- 5/16-18 U-BOLT
- U-BOLT SADDLE
- (2) 5/16 HEX NUTS
- (2) SPLIT LOCK WASHERS
- TYPICAL (4) CLAMPS

- (3) 5/16-18 BOLTS
- (3) 5/16 SPLIT LOCK WASHERS
- (1) ADAPTER RING, CAST 356 AL
- (1) MOUNTING RING (SUPPLIED BY LIGHT MFR.)
- (1) RUBBER SEAL
- TYPICAL (5) MOUNTS

- (2) 3/8-16 THREAD ENDS
- (2) 3/8 FLAT WASHERS
- (2) 3/8 SPLIT LOCK WASHERS
- (2) 3/8 HEX NUTS
- (2) CABLE STOPS

- (2) 3/8-16 BOLT
- (2) WASHER
- (2) SPLIT LOCK WASHER

- (1) 5/16-18 STUD
- (1) 5/16 HEX NUT
- (1) 5/16 SPLIT LOCK WASHERS
- (1) UPPER RETAINING RING
- (1) RUBBER SEAL

- (2) 5/16-18 U-BOLTS
- (2) 5/16 SPLIT LOCK WASHER
- (2) 5/16 HEX NUTS

POLE LENGTHS AVAILABLE
18", 24", 37", 46", 60", 74", 96", 120"

PART NUMBER

SS-SBC66-3MCB-46

CABLE LENGTH	MAST ARM DIA.
66"	3" - 7"
90"	7" - 11"
120"	12" - 15"
165"	15" - 22"

CABLE LENGTH _____

TUBE LENGTH _____

- NOTES:
1. STAINLESS STEEL HARDWARE.
 2. AVAILABLE WITH BAND STYLE CLAMP.

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SKYBRACKET. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SKYBRACKET IS PROHIBITED.



APPROVALS	BY	DATE
DRAWN	TRC	6/27/11
SALES		
ENGINEERING		
DO NOT SCALE DRAWING		

TITLE		3M STANDARD CLUSTER (CABLE CLAMP)	
SIZE	DWG. NO.	REV.	
A	SS-SBC66-3MCB-46	A	
SCALE: NTS/ CAD		FILE: SS-SBC66-3MCB-46	SHEET 1 OF 1