

ALUMINUM CHANNEL

5 PLCS:
 (1) 5/16-18 U-BOLT
 (1) U-BOLT SADDLE
 (2) 5/16 HEX NUTS

POLE TOP
 WIND DAMPER
 ADAPTER

SWIVEL
 CAST 356
 ALUMINUM

EXTRUDED ALUMINUM POLE

(2) 3/8-16 THREAD ENDS
 (2) 3/8 FLAT WASHER
 (2) 3/8 SPLIT LOCK WASHER
 (2) 3/8 HEX NUT
 (2) CABLE STOPS

(2) 5/16-18 U-BOLT
 (2) 5/16 SPLIT LOCK WASHER
 (2) 5/16 HEX NUT

CLAMP SADDLE ASSY.
 CAST 356 ALUMINUM

(2) 5/16-18 U-BOLT
 (2) U-BOLT SADDLE
 (4) 5/16 HEX NUTS
 (4) 5/16 SPLIT LOCK WASHERS

CABLE

(2) 3/8-16 BOLT
 (2) 3/8 FLAT WASHER
 (2) 3/8 SPLIT LOCK WASHER

PART NUMBER

SS-SBC66-SWD-46TK-23

POLE LENGTHS AVAILABLE

18", 24", 37", 46", 60"

CHANNEL LENGTHS AVAILABLE

8", 14", 23.5"

CABLE LENGTH

66"

90"

120"

MAST ARM DIA.

3" - 7"

7" - 11"

12" - 15"

NOTES:

1. STAINLESS STEEL HARDWARE.
2. AVAILABLE WITH BAND STYLE CLAMP.

CABLE LENGTH

TUBE LENGTH

CHANNEL LENGTH

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SKYBRACKET. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF SKYBRACKET IS PROHIBITED.



TITLE
**WIND DAMPER SS
 (CABLE CLAMP)**

APPROVALS	BY	DATE
DRAWN	TRC	7/19/16
SALES		
ENGINEERING		

SIZE	DWG. NO.	REV.
A	SS-SB66-SWD-46TK-23	A
DO NOT SCALE DRAWING		SCALE: NTS CAD FILE: SS-SB66-SWD-46TK-23 SHEET 1 OF 1